



# WORLD CARRIER CORPORATION

Agiassou 34, Vrilissia 15235, Athens, Greece

Tel : +30 210 80 35 835 Fax : +30 210 80 35 840 e-mail : info@worldcarrier.gr

www.worldcarrier.com



## M/T NOX

### Builders

SLOB, PAPENDRECHT, NL

### Year of Delivery

Mar 18, 1993

### Hull No.

9104

### Type

Double Hull Product Carrier

### Classification / Notation

Registro Italiano Navale/ C\* oil tanker ESP - double hull;  
unrestricted navigation Chemical tanker ESP-IMO 2

### Length Over All (LOA)

122.8 m

### Length Between Particulars (LBP)

117.71 m

### Breadth (Moulded)

16.7 m

### Depth (Moulded)

8.95 m

### Draft (Summer)

6.781 m

### GRT / NRT

5050 t / 2829 T

### Deadweight

9431 MT

### Lightship

2454.6 MT

### Accommodation

15 crewmen

### Speed / Consumption

13 Knots / 12 T/day

### Tanks Capacity

Cargo: 9906 m<sup>3</sup> at 98% excluding Slop Tanks

Slop: 25 m<sup>3</sup>

Ballast: 3292 m<sup>3</sup>

Diesel Oil: 176 m<sup>3</sup>

Fresh Water: 68T

### Propulsion System

1 - CCP HRP-52

### Main Engine

1 x KRUPP AK 8M453C, 4062 bhp

### M/E Turbo Charger

BBC VTR 304-II

### Diesel Generator

1 x 6BDXC-750-100A, BHP900/RPM 750

1 x SHAFT 680 KWS

### Emergency Generator

1 x 3412 KW583, RPM 1500

### Boiler

2 x 1,000KG/HR at 10 BARS

### Separators

2 x Fuel Oil Separator, 2 x Diesel Oil & 1 x Lub. Oil Separator

### Pumping System

Cargo pump: 6 x Deep well electrical driven pumps 280 m<sup>3</sup>/h

Stripping pump: 1 x 163m<sup>3</sup>/hr

Ballast pump: 2 x electrical driven pump 300 m<sup>3</sup>/h

### Manifolds

7 x 300mm

### Cargo Heating

All cargo tanks are coiled / Material of heating coil: Stainless steel

158F Max temperature cargo can be loaded

158F Max temperature cargo can be maintained

### Crane

1 x 2.2 Tonnes SWL Hydraulic

### Steering Gear

1 x hydraulic IPE 3-16101

### Anchor

2 x Fore castle

### Anchor Chains

1 x 9 shackles (stbd) - Fore castle 1 x 9 shackles (port)

### Windlass

Hydraulic

### Bow Thrusters

1 x 400kW

### Lifesaving / Firefighting

1 x Free fall/Boat 15 persons, 1 x Rescue boat 6 persons capacity

2 x L/Raft 20 & 16 persons capacity

1 x L/Raft 6 persons capacity

6 x Fire Monitor capacity 25m<sup>3</sup>/h across vessel's decks

### Navigation Equipment

ARPA Radar, Inmarsat-C, Navtex, EPIRB, Magnetic Compass,

Gyro Compass, GPS, AIS, Echo-sounder, VHF, ECDIS